Patent Claims

- A method for maintenance, in particular repair, of 1. gas turbines, in particular aeroengines, wherein 5 modules and/or assemblies and/or individual parts of the gas turbines, in particular aeroengines, are inspected and/or repaired, characterized that the repair is subdivided into at least two repair steps, wherein modules and/or assemblies 10 and/or individual parts to be repaired of at least one gas turbine are moved through repair stations in order to move the modules and/or assemblies and/or individual parts of the or each gas turbine to repair stations adapted for this purpose in 15 order to carry out the repair steps.
- 2. The method as claimed in claim 1, characterized in that the modules and/or assemblies and/or individual parts are repaired in different repair lines, with a decision being made after inspection of the modules and/or assemblies and/or individual parts on the repair line to which a module and/or assembly and/or individual part to be repaired will be sent.

25

30

35

- 3. The method as claimed in claim 1 or 2, characterized in that the repair of the modules and/or assemblies and/or individual parts in each of the repair lines is subdivided into at least two repair steps.
- method 4. The claimed in claim 2 3. as orcharacterized in that a coating-intensive repair line and/or a welding-intensive repair line and/or non-welding-intensive repair line are/is provided as repair lines.
- 5. The method as claimed in one or more of claims 1 to 4, **characterized** in that modules and/or

assemblies and/or individual parts of gas turbines, in particular aeroengines, are moved discontinuously, specifically on a cycle, through the repair stations or the repair lines.

5

10

15

30

35

- 6. The method as claimed in one or more of claims 1 to 5, characterized in that two or more repair steps are carried out in succession within one repair line, wherein the modules and/or assemblies and/or individual parts are moved to matched repair stations in order to carry out the repair identical steps, wherein two or more stations are provided for at least some of the repair steps, such that the same repair steps can be carried out at the same time on different modules and/or assemblies and/or individual parts within one repair line.
- 7. The method as claimed in one or more of claims 1 to 6, characterized in that, in addition to the repair stations in the repair lines, central repair stations are provided, wherein modules and/or assemblies and/or individual parts from different repair lines are passed to the central repair stations.
 - 8. The method as claimed in claim 7, characterized in that a heat treatment station and/or a washing station and/or an electroplating station are/is provided as central repair stations.
 - 9. The method as claimed in one or more of claims 1 to 8, characterized in that the modules and/or assemblies and/or individual parts are inspected after repair.
 - 10. The method as claimed in one or more of claims 1 to 9, **characterized** in that the gas turbines, in particular aeroengines, are disassembled into

modules and/or assemblies and/or individual parts before repair.

- 11. The method as claimed in one or more of claims 1 to 10, characterized in that, before being disassembled, the gas turbines, in particular the aeroengines, are precleaned as a unit, and in that the modules and/or assemblies and/or individual parts are preferably cleaned again before repair.
- 12. The method as claimed in one or more of claims 1 to 11, characterized in that gas turbines, in particular aeroengines, are assembled from inspected and/or repaired and/or new modules and/or assemblies and/or individual parts after repair.